


EXHIBIT 1




Installation Instructions for the QUICKRELT™ 50F Water Heater Restraints

1. Mark stud locations on both sides of heater within top and bottom thirds.
Bottom strap must clear controls by 4...
2. Attach end brackets to studs at marks with lags, noting orientation of brackets.




3. Join straps in front. A insert free end from behind and through front buckle.

B. Loop free end over front of buckle, back through second slot, and out through back of buckle. C. Dress loop and pull free end to remove slack. D. Press down on Quick Lock." to secure strap. F. ** ecure excess strap with supplied wire clip.



PACKAGE CONTENTS:

- 4 Straps
- 4 Lag Bolts
- 2 Wire Clips



WARNING:


Risk of damage or injury if concealed pipes or wiring are contacted during installation. If unsure seek qualified help.

BUCKLE RELEASE: Insert screwdriver into gap between front plate and side flange; just forward of each lock Twist gently while prying up: Pull up in thumb tab to free strap.

Full performance even if only one lock is engaged

SHEEFERTSH SEPARE SAN MO.

If not a "Zero Clearance" water heater back spacer is needed. Use or construct two spacers to meet water heater manufacturer's spacing requirements; one at each strap height. Lag. bolts must not attach to back spacers.



WARRANTY/DISCLAIMER

HUBBARD ENTEPRISES warrants this product to be free of defective material and workmanship for, as long as you own the water heater it secures. This is the full extent of our lifetime warranty. It is the responsibility of the user to make sure the restraint is properly installed "HUBBARD ENTERPRISES shall not be liable for improper, installations PATENT PENDING."

393 Enterprise Street, San Marcos, CA 92078 Phone: (800) 321-0316 www.holdrite.com